










ELECTROLUX, On-Off, Unitary Pro, R410a, 2013

Kasetiniai modeliai							
 	Vidinis / Išorinis	Galingumas, kW		Išmatavimai vidinio bloko, mm	Svoris, kg	Sistemos Kaina, Lt	
		Šaldymo	Šildymo			be PVM	su PVM
	EACC-12H U/N3 (220) / EACO-12H U/N3 (220)	3,5	3,6	600x600x230	20	2 567	3 106
	EACC-18H U/N3 (220) / EACO-18H U/N3 (220)	5	5,4	600x600x230	20	2 879	3 483
	EACC-24H U/N3 (220) / EACO-24H U/N3 (220)	6,8	7,5	840x840x240	27	3 991	4 829
	EACC-36H U/N3 (380) / EACO-36H U/N3 (380)	10	11	840x840x320	32	5 355	6 479
	EACC-42H U/N3 (380) / EACO-42H U/N3 (380)	12	14,1	840x840x320	32	5 655	6 843
	EACC-48H U/N3 (380) / EACO-48H U/N3 (380)	14,1	15,5	840x840x320	32	5 962	7 214
Konsoliniai (grandiniai/lubiniai) modeliai							
 	Vidinis / Išorinis	Galingumas, kW		Išmatavimai vidinio bloko, mm	Svoris, kg	Sistemos Kaina, Lt	
		Šaldymo	Šildymo			be PVM	su PVM
	EACU-18H U/N3 (220) / EACO-18H U/N3 (220)	5	5,7	836x695x238	26	2 847	3 444
	EACU-24H U/N3 (220) / EACO-24H U/N3 (220)	7	8	1300x600x188	33	3 786	4 582
	EACU-36H U/N3 (380) / EACO-36H U/N3 (380)	10	11	1590x695x238	48	5 183	6 271
	EACU-42H U/N3 (380) / EACO-42H U/N3 (380)	12	14,1	1590x695x238	48	5 451	6 596
	EACU-48H U/N3 (380) / ACO-48H U/N3 (380)	14,1	15,5	1590x695x238	48	5 827	7 051
Ortakiniai modeliai							
 	Vidinis / Išorinis	Galingumas, kW		Išmatavimai vidinio bloko, mm	Svoris, kg	Sistemos Kaina, Lt	
		Šaldymo	Šildymo			be PVM	su PVM
	EACD-09H/Eu / EACO-09H U/N3 (220)	2,6	2,85	913x220x680	26	2 105	2 547
	EACD-12H/Eu / EACO-12H U/N3 (220)	3,5	3,6	913x220x680	33	2 460	2 976
	EACD-18H/Eu / EACO-18H U/N3 (220)	5	5,7	1012x266x736	48	2 857	3 457
	EACD-24H/Eu / EACO-24H U/N3 (220)	7	8	1270x268x530	48	3 582	4 335
	EACD-36H/Eu / EACO-36H U/N3 (380)	9,8	11	1226x290x775	33	5 183	6 271
	EACD-48H/Eu / EACO-48H U/N3 (380)	14	15,5	1226x290x775	48	5 800	7 019
	EACD-60H/Eu / EACO-60H U/N3 (380)	16	18,5	1226x330x815	48	6 660	8 058
IŠORINIAI BLOKAI							
	Išorinis	Galingumas, kW		Išmatavimai išorinio bloko, mm	Svoris, kg		
		Šaldymo	Šildymo				
	EACO-09H U/N3 (220)	3,4	3,5	820x540x319	32		
	EACO-12H U/N3 (220)	3,5	3,6	820x540x320	32		
	EACO-18H U/N3 (220)	5	5,7	820x540x320	40		
	EACO-24H U/N3 (220)	7	8	1018x695x412	59		
	EACO-36H U/N3 (380)	10	11	1018x840x412	90		
	EACO-42H U/N3 (380)	12	14,1	1032x1250x412	112		
	EACO-48H U/N3 (380)	14,1	15,5	1032x1250x412	112		
	EACO-60H U/N3 (380)	16	18,5	1032x1250x413	120		