

INVERTER HEAT PUMP MODEL

Standard Series


SRK-ZMP

Wall Mounted type




SRK25ZMP-S, SRK35ZMP-S
SRK45ZMP-S

Refrigerant pipe length



SRK25ZMP-S
SRK35ZMP-S



SRK45ZMP-S

Standard equipment



SRK25ZMP-S
SRC35ZMP-S



SRK45ZMP-S

FUNCTION



Comfortable Functions



Comfortable Air Flow Functions



Convenient & Economy Functions



Maintenance & Prevention Functions



Others



SPECIFICATIONS

Indoor unit			SRK25ZMP-S	SRK35ZMP-S	SRK45ZMP-S
Outdoor unit			SRC25ZMP-S		SRC45ZMP-S
Power source			1 Phase, 220 - 240V, 50Hz		
Nominal cooling capacity (Min~Max)		kW	2.5(0.9~2.8)	3.2(0.9~3.5)	4.5(0.9~4.8)
Nominal heating capacity (Min~Max)		kW	2.8(0.8~3.9)	3.6(0.9~4.3)	5.0(0.8~5.8)
Power consumption		Cooling/Heating	kW		
EER/COP		Cooling/Heating			
Inrush current		220/230/240 V	A		
Max. running current			A		
* Sound power level	Indoor	Cooling/Heating	dB(A)		
	Outdoor	Cooling/Heating			
* Sound pressure level	Indoor	Cooling (Hi/Me/Lo)			
		Heating (Hi/Me/Lo)			
	Outdoor	Cooling/Heating			
		Cooling (Hi/Me/Lo)			
Air flow	Indoor	Heating (Hi/Me/Lo)	m ³ /min		
		Cooling/Heating			
	Outdoor	Cooling/Heating			
Exterior dimensions	Indoor	HeightxWidthxDepth	mm		
	Outdoor				
Net weight	Indoor / Outdoor	kg			
Ref.piping size	Liquid/Gas	ø mm			
Refrigerant line (one way) length		m			
Vertical height differences		Outdoor is higher/lower	m		
Outdoor operating temperature range		Cooling	°C		
		Heating			
Clean filter					

The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.